



## Disposable PFA Turbine flowmeter

This model is developed to perform a fast exchange of the flow tube (for hygienic reasons e.g. in pharmaceutical industry). The flowmeter is suitable for clear and opaque, neutral, corrosive and aggressive liquids, fuel and for periodic monitoring. The flow tube is assembled in the flow system. For measurement and calibration the easy-to-remove housing is placed around the tube and measuring can take place.

### Characteristics:

- Turbine flowsensor with high resolution output
- Flow Measuring by revolutionary IR turbine rotor reflection
- PFA / Teflon for high chemical and corrosive resistance
- High accuracy and repeatability ("swiss made")
- Suitable for opaque liquids
- Programmable pulse output
- PFA meet all the requirements of the US Pharmacopeia Class VI
- BSE/TSE certificate available

All wetted parts are made of Teflon®/PFA with ruby bearing.  
The flow tube can be sterilised up to 160° C.



Patent US5388466

### Options:

- Programmable K-factor
- Flow Alarm level
- Batchfunction with preset

Model	0045	0085
Inner diameter in mm	4,5	8,5
Flow range	0,06 – 2 L/min	0,5 – 20 L/min
Accuracy	1% of reading	1% of reading
Repeatability	< 0,15 %	< 0,15 %
Wetted parts	PFA / Ruby	PFA / Ruby
Tube connection	1/8" NPT or 7 mm hosebarb	1/4" NPT or 12 mm hosebarb
Tube length in mm	L. 51	L. 60
Liquid temperature in °C	-20 tot +80	-20 tot +80
Max. pressure at 20°C in MPa	2 (20 Bar)	1,5 (15 Bar)
Viscosity in cSt.	0,8 - 10	0,8 – 10
K factor (water) in pulse/Litre	110.000	6.100
Power supply	5 - 30 Vdc	5 - 30 VDC
Output signal	5 - 30 V square wave	5 - 30 V square wave
Power consumption	34 mA at 5 V	34 mA at 5 V
Electrical cable lenght	PVC 1 meter	PVC 1 meter
Other Specs on request.		

Subject to change without notice 10.2011